

Magellan 1500i OEM	
Magellan 1500i, Black, OEM Configuration, 2D	MG1503-30200
Magellan 1500i, Black, OEM Configuration, 2D, USB A Cable	MG1503-30200-0200
Magellan 1500i, Black, OEM Configuration, 2D, Wall Mount Kit, USB A Cable	MG1503-30250-0200

EASEOFCARE AGREEMENTS	
MAGELLAN 1500i EofC 5 DAYS RENEWAL	ZSN5M1500R1
MAGELLAN 1500i EofC, 2 DAYS COMPREHENSIVE, 3 YEARS	ZSC2M150031
MAGELLAN 1500i EofC, 2 DAYS COMPREHENSIVE, 5 YEARS	ZSC2M150051
MAGELLAN 1500i EofC, 2 DAYS COMPREHENSIVE, RENEWAL	ZSC2M1500R1
MAGELLAN 1500i EofC, 5 DAYS, 3 YEARS	ZSN5M150031
MAGELLAN 1500i EofC, 5 DAYS, 5 YEARS	ZSN5M150051
MGL 1500i EofC OVERNIGHT REPLACEMENT, COMPREHENSIVE, 3 YEARS	ZSC1M150031
MGL 1500i EofC OVERNIGHT REPLACEMENT, COMPREHENSIVE, 5 YEARS	ZSC1M150051
MGL 1500i EofC OVERNIGHT REPLACEMENT, COMPREHENSIVE, RENEWAL	ZSC1M1500R1

CABLES	
CABLE ASY,RS,9D,S,E/P,EAS,SHT/OM,2M	90A052338
Cable, IBM USB, Power Off Terminal, Straight, 2 m	8-0754-07
CABLE, RS AUX, RJ10P, STRT, 2M	90A052346
Cable, RS-232, External Power, 9D, S, 2 m	8-0751-11
Cable, RS-232, Ruby Verifone, 8RJ, P, External Power, Straight, 2 m	8-0751-16
Cable, RS-232, Wincor w/DTR, 2 m	8-0751-10
Cable, USB, Power Off Terminal, Coiled, 2.44 m	8-0754-15
Cable, USB, Type A, Power Off Terminal, 2 m	8-0754-12
CABLE, USB+ POT, COIL, 3.65M	90A052351
Cable,IBM, USB,Power Off Terminal,Straight,3.66M	8-0754-13
CABLE,USB, POT,COIL,3.6M	90A052364

CABLE,USB,OEM,POT,EAS,2M	90A052337
CABLE,USB,SERIES A,POT,1M	90A052363
CABLE,USB,SERIES A,POT,EAS,2M	90A052336
CABLE,USB,SERIES A,STRAIGHT,3.66M	8-0754-14
CBL,RS232 9D S, E/P, SHT/OM, 600mm	90A052369

MOUNTS/STANDS	
	ACCESSORY,WALL MOUNT KIT,BLK,MGL15 90ACC0382
	ROUND STAND, BLACK BASE, BLACK SCANNER 90ACC0400
	ROUND STAND, SILVER BASE, BLACK SCANNER 90ACC0402
	ROUND STAND, SILVER BASE, WHITE SCANNER 90ACC0401

POWER SUPPLIES/CORDS	
Power Cord, 2-Pin, AU	90ACC0316
Power Cord, 2-Pin, China	90ACC0311
Power Cord, 2-Pin, EU	90ACC1885
Power Cord, 2-Pin, Japan	90ACC0312
Power Cord, 2-Pin, UK	90ACC1887
Power Cord, 2-Pin, US	90ACC1886
Power Supply, 5VDC, includes 2 pin power cord adapter, no power cord	90ACC0287