

| Gryphon GFS4500 Series | |
|--|------------------|
| CBL USB2.0 A/M TO MICRO B/M,3M,BK,SH6382 | 90A052403 |
| CBL USB2.0 A/M TO MICRO B/M,5M,BK,SH6382 | 90A052404 |
| Gryphon I GFE4590, 2D, MP, Red illumination, 5-14V, USB/RS232, 12pin connector, OEM decoded scan engine | GFE4590-RED |
| Gryphon I GFS4520, 2D, MP, Red illumination, 5V, USB-only, microUSB connector, Black | GFS4520-BK-RED |
| Gryphon I GFS4520, 2D, MP, White illumination, 5V, USB-only, microUSB connector, Black | GFS4520-BK-WHT |
| Gryphon I GFS4520, Kit, 2D, MP, Red illumination, 5V, USB-only, microUSB connector, Black (Kit includes Scanner and USB Cable 94A051968) | GFS4520-BKK1-RED |
| Gryphon I GFS4520, Kit, 2D, MP, White illumination, 5V, USB-only, microUSB connector, Black (Kit includes Scanner and USB Cable 94A051968) | GFS4520-BKK1-WHT |
| Gryphon I GFS4550, 2D, MP, Red illumination, 5-14V, RS232-only, 2m cable DB9 connector, Black | GFS4550-BKK2-RED |
| Gryphon I GFS4590, 2D, MP, Red illumination, 5-14V, USB/RS232, 10 cm cable RJ50 connector, Black | GFS4590-BK-RED |

| EASEOFCARE AGREEMENTS | |
|--|-------------|
| Gryphon GFS4500 EofC 2 Days Comp 1 Yr, R | ZSC2GFS45R1 |
| Gryphon GFS4500 EofC 2 Days Comp 5 Yr | ZSC2GFS4551 |
| Gryphon GFS4500 EofC 5 Days, 1 Yr, Renew | ZSN5GFS45R1 |
| Gryphon GFS4500 EofC 5 Days, 5 Years | ZSN5GFS4551 |
| Gryphon GFS4500 EofC Ovrhnt Rplce 1 Yr R | ZSC1GFS45R1 |
| Gryphon GFS4500 EofC Ovrhnt Rplcmnt 5 Yr | ZSC1GFS4551 |

| CABLES | |
|---|-----------|
| Cable from Micro USB (device or dock) to USB. Device works as client. 2m straight cable. | 94A051968 |
| Cable, RS-232, 12' Coiled (For Magellan) | 90G001095 |
| Cable, RS-232, 9P, Female, Coiled, CAB-362, External Power, 6 ft. | 90A051330 |
| Cable, RS-232, 9P, Female, Coiled, CAB-408 (Power available on pin 9 of the connector or through external power supply), 6 ft. | 90A051891 |
| Cable, RS-232, 9P, Female, Straight, CAB-327, Requires External Power, 6 ft. | 90G000008 |
| Cable, RS-232, 9P, Female, Straight, CAB-350 (Power Supply available on pin 9 of the connector or through external power supply), 6 ft. | 90A051230 |

| | |
|---|-----------|
| Cable, RS-232, 9P, Male, Beetle POS, Straight, CAB-389, Power Off Terminal, 6.5 ft. | 90A051710 |
| Cable, RS-232, DCE, 9P, Extended Power-Power off Terminal, 4 Meters | 90A052086 |
| Cable, RS-232,6' (For Magellan) | 90G001092 |
| Cable, USB, Power Conn, Straight, Power off terminal, 2 Meters, CAB-413E2 | 90A052101 |
| Cable, USB, Type A, Coiled, Power off terminal, 2 Meters, CAB-424E | 90A052100 |
| Cable, USB, Type A, Enhanced, Coiled, Power Off Terminal, 5 Meters | 90A052066 |
| Cable, USB, Type A, Enhanced, Straight, Power Off Terminal, 2M (USB Certified) | 90A052065 |
| Cable, USB, Type A, External Power, High Current, PVCW, Straight, 1.2M, Black (for use with WLC4X90 Wireless Charging Base Station) | 90A052361 |
| Cable, USB, Type A, External Power, High Current, PVCW, Straight, 3M, Black (for use with WLC4X90 Wireless Charging Base Station) | 90A052356 |
| Cable, USB, Type A, PVCW, Straight, 2M, Black | 90A052258 |
| Cable, USB, Type A, PVCW, Straight, 2M, White | 90A052278 |
| Cable, USB, Type A, TPUW, Coiled, Power off Terminal, 5M, Black | 90A052289 |
| Cable, USB, Type A,TPUW, Coiled, 2.4m, Black | 90A052285 |
| Cable, USB, Type C, High Current, PVCW, Straight, 1.2M, Black (for use with WLC4190 Wireless Charging Base Station) | 90A052360 |
| Cable, USB, Type C, High Current, PVCW, Straight, 3M, Black (for use with WLC4190 Wireless Charging Base Station) | 90A052355 |
| Cable, USB, Type C, PVCW, Coiled 2.4M, Black | 90A052354 |
| Cable, USB, Type C, PVCW, Straight, 2M, Black | 90A052352 |
| Cable, USB, Type C, PVCW, Straight, 2M, White | 90A052353 |
| Cable, USB+PWR,TPUW, Straight, 2M, Black | 90A052302 |
| CABLE,RS232,DB9,OUTPUT,GFS4450-9, 2M | 90A052318 |
| CABLE,USB,OUTPUT,GFS4470,2M | 90A052324 |

| | |
|--|------------|
| MOUNTS/STANDS | |
| Mounting Adapter to replicate the GFS4400 fixing holes | MA-4500-BK |