

DSM04XX	
DSM0400, 2D, MP-DL, RS-232 and USB, RJ-45 Connector	DSM0492-DL
DSM0400, 2D, MP-DL, RS-232, 2 m Cable	DSM0452-DL
DSM0400, 2D, MP-DL, USB, 50 cm Cable	DSM0422-DL
DSM0400, 2D, MP-SR, USB, 50 cm Cable	DSM0422-SR
DSM0400, 2D, MP-WA, RS-232 USB, RJ-45 Connector	DSM0492-WA
DSM0400, 2D, MP-WA, RS-232, 2 m Cable	DSM0452-WA
DSM0400, 2D, MP-WA, USB, 50 cm Cable	DSM0422-WA
DSM0400, 2D, WVGA, USB, 50 cm Cable	DSM0421

EASEOFCARE AGREEMENTS	
DSM04XX EofC OVERNIGHT RPLCMT COMP 3 YRS	ZSC1DSM04XX31
DSM04XX EofC OVERNIGHT RPLCMT COMP 5 YRS	ZSC1DSM04XX51
DSM04XXi EofC 2 DAYS COMP 3 YRS	ZSC2DSM04XX31
DSM04XXi EofC 2 DAYS COMP 5 YRS	ZSC2DSM04XX51
DSM04XXi EofC 5 DAYS 3 YRS	ZSN5DSM04XX31
MINIMUM REPAIR CHARGE, DSM04XX	ZR0DSM04XXMIN

CABLES	
Cable, RS-232, 9P, Female, Straight, CAB-350 (Power Supply available on pin 9 of the connector or through external power supply), 6 ft.	90A051230
Cable, USB, Type A, Enhanced, Straight, Power Off Terminal, 2M (USB Certified)	90A052065

MISCELLANEOUS	
GFS ADAPTER PLATE, DSM04XX	901340002

POWER SUPPLIES/CORDS	
ADAPTER, POWER PLUG, AUSTRALIA	90ACC0309
ADAPTER, POWER PLUG, EURO, 2 PIN	90ACC0307
ADAPTER, POWER PLUG, UK	90ACC0308
ADAPTER, POWER PLUG, US/JAPAN	90ACC0306
Power Cord, 2-Pin, EU	90ACC1885
Power Cord, 2-Pin, UK	90ACC1887
Power Cord, 2-Pin, US	90ACC1886
Power Supply, 5VDC, includes 2 pin power cord adapter, no power cord	90ACC0287