

| TD1100 Lite Models and Kits | |
|--|----------------|
| TD1100 65 Lite, Black, RS-232/KBW Interface | TD1170-BK-65 |
| TD1100 65 Lite, Black, USB Interface | TD1120-BK-65 |
| TD1100 65 Lite, Black, USB Kit (Includes Scanner, Holder and 90A052065 Cable.) | TD1120-BK-65K1 |

| TD1100 Pro Models and Kits | |
|---------------------------------------|--------------|
| TD1100 65 Pro, Black, Multi-Interface | TD1130-BK-65 |



| TD1100 Lite Models and Kits | |
|--|----------------|
| TD1100 90 Lite, Black, RS-232/KBW Interface | TD1170-BK-90 |
| TD1100 90 Lite, Black, USB Interface | TD1120-BK-90 |
| TD1100 90 Lite, Black, USB Kit (Includes Scanner, Holder and 90A052065 Cable.) | TD1120-BK-90K1 |

| TD1100 Pro Models and Kits | |
|---------------------------------------|--------------|
| TD1100 90 Pro, Black, Multi-Interface | TD1130-BK-90 |

| EASEOFCARE AGREEMENTS | |
|--|-------------|
| TD1100 EofC 2 Days Comprehensive, 5 Years | ZSC2TD11X51 |
| TD1100 EofC 5 Days, 5 Years | ZSN5TD11X51 |
| TD1100 EofC Overnight Replacement Comprehensive, 5 Years | ZSC1TD11X51 |

| CABLES | |
|--|-----------|
| CAB-424E ENHANCED USB TYPE A, 9' COILED | 90A052043 |
| Cable, IBM PS/2, KBW, Minidin Connector, Coiled, CAB-365, 6 ft. | 90A051360 |
| Cable, RS-232, 25P, Female, Coiled, CAB-363 (Power available on pin 9 of the connector or through external power supply), 6 ft. | 90A051340 |
| Cable, RS-232, 25P, Female, Straight, CAB-328 (Power Supply available on pin 9 of the connector or with external power supply), 2 Meters | 90G001080 |
| Cable, RS-232, 25P, Male, Coiled, CAB-364 (Power Supply available on pin 9 of the connector or through external power supply), 6.5 ft. | 90A051350 |

| | |
|---|-----------|
| Cable, RS-232, 9P, Female, Coiled, CAB-362, External Power, 6 ft. | 90A051330 |
| Cable, RS-232, 9P, Female, Coiled, CAB-408 (Power available on pin 9 of the connector or through external power supply), 6 ft. | 90A051891 |
| Cable, RS-232, 9P, Female, Straight, CAB-327, Requires External Power, 6 ft. | 90G000008 |
| Cable, RS-232, 9P, Female, Straight, CAB-350 (Power Supply available on pin 9 of the connector or through external power supply), 6 ft. | 90A051230 |
| Cable, RS-232, 9P, Male, Beetle POS, Straight, CAB-389, Power Off Terminal, 6.5 ft. | 90A051710 |
| Cable, RS-232, 6' (For Magellan) | 90G001092 |
| Cable, USB, Type A, Coiled, Power off terminal, 2 Meters, CAB-424E | 90A052100 |
| Cable, USB, Type A, Enhanced, Straight, Power Off Terminal, 2M (USB Certified) | 90A052065 |

| MOUNTS/STANDS | | |
|--|--------------------------------|----------------|
|  | Holder, Desk/Wall for Touch 65 | HLD-T010-65-BK |
|  | Holder, Desk/Wall for Touch 90 | HLD-T010-90-BK |

| POWER SUPPLIES/CORDS | |
|---|-----------|
| Power Cord, 2-Pin, EU | 90ACC1885 |
| Power Cord, 2-Pin, UK | 90ACC1887 |
| Power Cord, 2-Pin, US | 90ACC1886 |
| Power Supply, 5VDC, ready to accept 2 pin power cord or alternatively an adapter power plug (not included order separately) | 90ACC0287 |

| | |
|--|--------------|
| SOFTWARE | |
| SOTI MobiControl Enterprise Support per device per month (>=500 devices). Requires ZSSOTISTDMTC as well. | ZSSOTIENTMTC |