

<b>TD1100 Lite Models and Kits</b>	
TD1100 65 Lite, Black, RS-232/KBW Interface	TD1170-BK-65
TD1100 65 Lite, Black, USB Interface	TD1120-BK-65
TD1100 65 Lite, Black, USB Kit (Includes Scanner, Holder and 90A052065 Cable.)	TD1120-BK-65K1

<b>TD1100 Pro Models and Kits</b>	
TD1100 65 Pro, Black, Multi-Interface	TD1130-BK-65



<b>TD1100 Lite Models and Kits</b>	
TD1100 90 Lite, Black, RS-232/KBW Interface	TD1170-BK-90
TD1100 90 Lite, Black, USB Interface	TD1120-BK-90
TD1100 90 Lite, Black, USB Kit (Includes Scanner, Holder and 90A052065 Cable.)	TD1120-BK-90K1

<b>TD1100 Pro Models and Kits</b>	
TD1100 90 Pro, Black, Multi-Interface	TD1130-BK-90

<b>EASEOFCARE AGREEMENTS</b>	
TD1100 EofC 2 Days Comprehensive, 5 Years	ZSC2TD11X51
TD1100 EofC 5 Days, 5 Years	ZSN5TD11X51
TD1100 EofC Overnight Replacement Comprehensive, 5 Years	ZSC1TD11X51

<b>CABLES</b>	
CAB-424E ENHANCED USB TYPE A, 9' COILED	90A052043
Cable, IBM PS/2, KBW, Minidin Connector, Coiled, CAB-365, 6 ft.	90A051360
Cable, RS-232, 25P, Female, Coiled, CAB-363 (Power available on pin 9 of the connector or through external power supply), 6 ft.	90A051340
Cable, RS-232, 25P, Female, Straight, CAB-328 (Power Supply available on pin 9 of the connector or with external power supply), 2 Meters	90G001080
Cable, RS-232, 25P, Male, Coiled, CAB-364 (Power Supply available on pin 9 of the connector or through external power supply), 6.5 ft.	90A051350

Cable, RS-232, 9P, Female, Coiled, CAB-362, External Power, 6 ft.	90A051330
Cable, RS-232, 9P, Female, Coiled, CAB-408 (Power available on pin 9 of the connector or through external power supply), 6 ft.	90A051891
Cable, RS-232, 9P, Female, Straight, CAB-327, Requires External Power, 6 ft.	90G000008
Cable, RS-232, 9P, Female, Straight, CAB-350 (Power Supply available on pin 9 of the connector or through external power supply), 6 ft.	90A051230
Cable, RS-232, 9P, Male, Beetle POS, Straight, CAB-389, Power Off Terminal, 6.5 ft.	90A051710
Cable, RS-232,6' (For Magellan)	90G001092
Cable, USB, Type A, Coiled, Power off terminal, 2 Meters, CAB-424E	90A052100
Cable, USB, Type A, Enhanced, Straight, Power Off Terminal, 2M (USB Certified)	90A052065

MOUNTS/STANDS		
	Holder, Desk/Wall for Touch 65	HLD-T010-65-BK
	Holder, Desk/Wall for Touch 90	HLD-T010-90-BK

POWER SUPPLIES/CORDS	
Power Cord, 2-Pin, EU	90ACC1885
Power Cord, 2-Pin, UK	90ACC1887
Power Cord, 2-Pin, US	90ACC1886
Power Supply, 5VDC, ready to accept 2 pin power cord or alternatively an adapter power plug (not included order separately)	90ACC0287

<b>SOFTWARE</b>	
SOTI MobiControl Enterprise Support per device per month (>=500 devices). Requires ZSSOTISTDMTC as well.	ZSSOTIENTMTC