

## **Ruby Verifone Terminal Setup**

The Ruby Verifone can be configured with different settings than what is listed on this sheet, please keep in mind this is the most commonly used configuration but may differ from the setting on your terminal.

This scan sheet will work for the following scanners.

- Gryphon™ D432(+)/D412(+)
- Powerscan™ PD8530
- Powerscan™ PM8500

Scan barcodes below in order.

1.

Set RS-232 Interface



2.

Enable Verifone specific COM settings



Datalogic has taken reasonable measures to provide information in this Programming Aid that is complete and accurate. However, Datalogic reserves the right to change any specification at any time without prior notice. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Scanning Inc. is under license. © 2010 Datalogic Scanning Inc. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic ADC. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S.A. and the E.U. 3GL, Datalogic STAR Cordless System, and Touch are trademarks of Datalogic ADC S.r.l. • Magellan, PowerScan, and Quick Scan are registered trademarks of Datalogic ADC. In many countries, including the U.S.A. and the E.U. All Weighs, Cashier Training, FirstStrike, Heron, Gryphon, PreScan, Produce Rail, Productivity Reporting, and SurroundScan, are trademarks of Datalogic ADC. • All other brand and product names are trademarks of their respective owners. Product specifications are subject to change without notice.